

Higher Handling Capacity – Lower Costs

The machine has been designed specifically for handling bulk and general cargo. What sets it apart is its extremely high load capacities combined with a very long reach. The new weight-optimized attachment makes the machine highly effective in operation, guaranteeing maximum performance at minimum cost per tonne of material handled. The modular structure of the basic machine and attachment offers optimal solutions for all operations.

Highest Handling Capacity

Performance

The 4 cylinder Liebherr in-line diesel engine returns together with the ERC system a total system performance of 322 kW, which assures maximum handling output.

Weight-Optimized Attachment

The newly-designed attachment for port application enables an extremely high load capacity. The attachment's weight is optimized thanks to a new design. The ERC, hoist and stick cylinders are adapted to the operating conditions.

Stability

The counterweight in the base unit is tailored to the special operating conditions of a port-based machine. The optimized weight distribution between the uppercarriage, undercarriage and attachment ensures stability with maximum load capacity.


Fuel Efficiency

Engine Idling and Engine Shut Down

The standard automatic idling function reduces the engine speed to idle as soon as the operator takes their hand from the joystick so that no hydraulic function is activated. Proximity sensors in the joystick levers restore the original engine speed as soon as the operator's hand is moved towards the lever again. This ensures that the set engine speed is available immediately. This results in both fuel saving and reduced noise levels. Operating costs can be reduced even further with the optional automatic engine shut down function.

Closed Hydraulic Circuit for the Swing Mechanism

The closed slewing circuit feeds the braking energy back into the system when the uppercarriage is braked. This simple yet effective feature sets new standards in terms of efficiency and economy.



Attachment

- Weight-optimized design for greatest load capacities
- Large working area created by a reach of up to 75'6"
- Electro-hydraulic end position control prolongs service life of components
- Quick coupling system guarantees maximum flexibility

Hydraulic System

- Work functions are electrically piloted for optimum controllability
- Load-Sensing-System LUDV enables maximum efficiency
- Huge system performance thanks to the energy recovery system ERC

Low Fuel Consumption Thanks to Intelligent Machine Control

- Liebherr-Power Efficiency (LPE) optimizes the interaction of the drive components in terms of efficiency
- LPE enables machine operation in the area of the lowest specific fuel use for less consumption and greater efficiency with the same performance

LIEBHERR




Liebherr ERC-System



ERC System – More Performance, Less Consumption

Lowering the equipment fitting stores energy in the ERC system. This stored energy is then made available to the machine to provide additional engine power. When the equipment is raised the stored energy is released and is reflected in

powerful, homogeneous operating cycles. The result is a clear saving on fuel – and, at the same time, even greater performance.



System Power

The energy recovery cylinder is a storage system which is independent of the diesel engine. The system performance of material handling machines fitted with the ERC system is composed of the installed engine power and the energy recovery cylinder. When the equipment is raised, energy from the ERC system is supplied in addition to the power from the diesel engine.

